WearDetect

Oil Debris Sensor

Real-time ferrous wear detection – discover machinery failures faster



gillsc.com

3002-291 Issue 2 © 2021 Gill Sensors & Controls Limited





DETECTING MACHINERY FAILURES FASTER

fum

WearDetect Oil Debris Sensor is proven in use by some of the world's leading manufacturers, to provide the earliest warning of the initial stages of machine failure.

DAILY OIL HEALTH CHECK

Provides a "daily" check into the condition of your machine

NO EXPENSIVE TRAINING PROGRAMS

No expensive training programs or expert knowledge to interpret the results, unlike most other technologies in the condition monitoring field.

SMART MAGNETIC DRAIN PLUG

Replace the existing drain plug with WearDetect Oil Debris Sensor and wire into your PLC or SCADA system. Alternatively use our "inflow" adaptor to install the sensor in the oil flow line, before any filters.

PREDICT AND SCHEDULE MAINTENANCE ACTIONS

Use the data from WearDetect to predict and schedule maintenance actions. From determining the need to increase the frequency of lab oil samples to full machine shutdowns, WearDetect is always on guard.



lost \$1,000?

How long before you have lost \$10,000?

microscope?

In most large industrial factories \$1,000 can be lost in less than half an hour. If you invested \$1,000 in a device with the capability to monitor your assets 24 hours a day 7 days a week how many minutes of downtime would it have to save to pay for itself? Not many.



gillsc.com 3002-291 Issue 2 © 2021 Gill Sensors & Controls Limited

Herbertek www.herbertek.se info@herbertek.se +46-18 590510

WearDetect Oil Debris Sensor comprises of two key elements. The sensor probe, that comes with multiple thread adaptor options, is coupled with the gearbox in place of the standard magnetic drain plug. The probe is then connected by wire to the separate electronics module, which turns the sensor signals into useful data. This data is then relayed via analogue or digital communications protocols for display or post processing. The electronics enclosure is available in a premium option which includes a local, high intensity, LED scale to display the captured debris levels.

How long would a critical asset need to be shutdown before you

How long before reliability is under the management





Product Trials

Product Success

Four of the top five largest global manufacturing companies have tested WearDetect and are running active installation programs on key manufacturing assets.

One particular customer turned to Gill to solve a problem that they could not trace in time with vibration sensing.

Top 5 largest manufacturing companies by revenue.

No.	Company Name	Revenue (by US\$ m)
1	Volkswagen Group	288,888
2	Toyota Group	265,172
3	Apple	229,234
4	Samsung	211,940
5	Daimler	185,235

Ref CNN Money – Fortune 500 global

WearDetect outperformed the company's vibration sensors in their speed reducer gearbox application. The images below show damage that has occured on the asset, which was not picked up by the company's vibration sensors. If it wasn't for WearDetect the damage could have been catastrophic.







Heavy polishing

Filter Bypass Line "inflow"

WearDetect Oil Debris Sensor was trialled by one of the top 5 Fortune 500 companies.

The sensor was trialled side by side against oil acidity sensors and vibration sensors in accelerated destructive tests.

The graphic above shows that the sensor outperformed other technologies detecting failures significantly earlier.

Did you know?

Real-time analysis of oil condition has been identified by independent assessors as the fastest growing sensor technology in the condition-based monitoring industry.

Ref Bureau Veritas - SMRP Conf. 2019

Product Review

What our customers say:

"Our [WearDetect] sensor shows that fine particles had increased before abnormal vibration. We used a device capable of real-time vibration frequency analysis, and the [WearDetect] oil sensor reacted before the [vibration manufacturer] sensor did."

- Reliability engineer | top 5 Fortune 500 list of largest manufacturing companies.





Sump Installation



gillsc.com 3002-291 Issue 2 © 2021 Gill Sensors & Controls Limited





Correlation Of Results From Fine & Coarse Debris Sensing, Laboratory Oil Sampling & Vibration A





Easy to install

How to set up

WearDetect Oil Debris Sensor can be installed 'out of the box'. If you want to adjust the sensor parameters, Gill provide a free to download and use Windows application with a handy setup wizard. See the support pages of www.gillsc.com for details. You will also find a training video on our YouTube channel.

Typical Applications

- Gearboxes
- Engines
- Hydraulics
- Differential Gears

Transmissions

Final Drives

- Speed Reducers
- Planetary gears
- Track Drives

How does WearDetect measure up against competitive technologies?

There are so many condition monitoring technologies in market, maybe you already have some of these installed. So, how does WearDetect Oil Debris Sensor measure up?



Application Story

One of the UK's largest manufacturers of own label chilled pizza, with a 43% market share, relies on high production availability to meet the freshness and just-in-time delivery requirements of its customers. The costs, reputational damage of unplanned downtime, and consequent supply disruption are so significant that the company invests in WearDetect in order to protect both its reputation and profits.

Installed on the company's operationally critical gearboxes, a suite of WearDetect sensors are protecting the assets of one of the UK's most loved food production lines. [Read full story]



Ultimate Solution

Did you know that an optimum condition based monitoring assessment should be made by comparing multiple data points? That means that lab oil analysis, and WearDetect, Oil Debris Sensor, can work hand in glove for the ultimate analysis suite.





gillsc.com 3002-291 Issue 2 © 2021 Gill Sensors & Controls Limited

Herberte





www.herbertek.se info@herbertek.se +46-18 590510



Product Range



WearDetect with display

Sensor with display models	
Oil Debris Sensor with Display 4-20mA	
Oil Debris Sensor with Display 0-10v	
Oil Debris Sensor with Display CAN	

Sensor head fittings		
Sensor Head Fitting M22x1.5 6g to BS3643		
Sensor Head Fitting M24x2.0 6g to BS3643		
Sensor Head Fitting 3/4" x 16UNF class 2a to ASME/ANSI B1.1		
Sensor Head Fitting 1/2"BSPP to BS EN ISO 228-1		
Sensor Head Fitting M20x1.5 6g to BS3643		



WearDetect without display

Sensor without display models
Oil Debris Sensor 4-20mA
Oil Debris Sensor 0-10v
Oil Debris Sensor CAN

Options	
Inflow Adaptor for M20 x 1.5 sized sensor	
Inflow Adaptor kit with Valves for 1" diameter pipe	
Inflow Adaptor kit with Valves for 1.5" diameter pipe	
Conduit kit for display models (Sensor to electronics)	
Demonstration Kit	



Adaptor kit (sensor not included)

Where to buy



Adaptor (sensor not included)

Gill sells its products through a worldwide network of trained <u>distributors</u>, so you can count on the very best advice for your application.

For further information on WearDetect Oil Debris Sensor range, including manuals and datasheets, please click below.

> Technical Specifications

Herbertek www.herbertek.se info@herbertek.se +46-18 590510



